



Model 170

Automatic Audiometer

- Automatic and manual audiometry
- Printout with optional printer
- Compact and easy to use
- Talk forward function
- Data analysis with optional Audibase PC software
- Reduced test time
- Totally portable
- Weighs just 700g
- User defined test frequency range
- Optional carrying case for mobile use

The **Amplivox 170** is a low cost screening audiometer offering both automatic and manual audiometry.

Improved Use

The **Amplivox 170** is ideal for occupational or workplace health and primary care audiometric requirements. Upon test completion, results can be printed with the optional printer, saved in memory for future use, recorded manually or transferred to a PC installed with Amplivox audibase software for electronic storage and statistical analysis of audiogram results.

Totally Portable

Lightweight and compact, the **Amplivox 170**, weighs just 700g and is totally portable. It is ideal for both desktop and mobile needs.

Ergonomic Design

Laid out in an ergonomic manner, the control panel is clear, easy to read and very easy to use with all settings and results displayed on the integral display. The **Amplivox 170** is designed and manufactured to conform with the relevant international audiometric and safety standards.





Standard equipment

- Audiometric headset
- Patient response switch
- Audiogram cards (50)
- Operating manual
- Mains power adaptor

Optional equipment

- Designated external printer and cable
- Audibase PC software and cable
- USB adaptor
- Audiometer carrying case
- Audiocups (noise reducing earphone enclosures)
- Audiogram cards
- Insert earphones



Carrying case

For mobile requirements the **Amplivox 170** can be supplied with the optional audiometer carrying case



Portable printer

For a fast and efficient recording of test information, a lightweight, thermal printer can be supplied.

Technical Specification

OUTPUT/INPUT DATA

Outputs:	Left AC, Right AC
Frequency range (Hz):	250*, 500, 1K, 1K5*, 2K, 3K, 4K, 6K, 8K*
	<i>*may be individually selected for automatic test</i>
Frequency accuracy:	<1%
Distortion:	<2%
Output level range (AC):	-10dBHL to 100dBHL (max)
Output level accuracy:	Within 3dB
Output level step size:	5dB
Test modes:	Automatic Manual
Internal memory:	12 complete tests
Designated printer:	Martel MCP8830

PHYSICAL DATA

Graphic display:	2 lines of 24 characters
Power (mains):	90-240V ac 50/60 Hz
Dimensions (mm):	252 x 175 x 63 high
Weight:	700 grams

STANDARDS

The Amplivox 170 conforms to the relevant clauses of the following standards.

Safety:	EN60601-1
EMC:	EN60601-1-2
Audiometric:	EN60645
CE mark:	Approved for Medical Device Directive

The Amplivox policy is one of continuous development and consequently the equipment may vary in detail from the description and specification in this publication.

Model 170
Automatic Audiometer



Amplivox Ltd, 29-30 Station Approach
Kidlington, Oxford, England, OX5 1JD
Tel: +44 (0)1865 842411
Fax: +44 (0)1865 841853
E-mail: sales@amplivox.ltd.uk
Website: www.amplivox.ltd.uk

Distributed by:



1/10 Dorsey Street, Milton, QLD 4064
PO Box 1869, Toowong DC, QLD 4066
Free call: 1800 639 263 F 07 3368 1044
E enquiry@sonici.com.au
W www.sonici.com.au