

easyTymp - Handheld Screening Tympanometer with Reflex Tests



- Very fast and reliable Impedance measurement
- Probe tone 226 Hz, optional high frequency probe tone 1 kHz
- Reflex frequencies 500 Hz, 1 kHz, 2 kHz, 4 kHz
- Automatic tests - self-explanatory to use
- Full color, high resolution display
- Stores more than 1000 measurements

easyTymp - Handheld Screening Tympanometer with Reflex Tests

Very fast middle ear measurements

The easyTymp is the ideal handheld device for middle ear screening tests. It performs reliable impedance and ipsilateral reflex tests within seconds.

The intensity of the four frequencies of the reflex test is increased automatically until a reflex is detected or the maximum is reached.

Select Protocol

All available test protocols can be easily selected with one hand. Available test protocols: Tympanometry with 226 Hz; Tympanometry and Auto Reflex or Tympanometry with Reflex at 90 dB.

Optional high frequency tympanometry

The optional high frequency probe tone of 1 kHz is ideal for providing reliable results when testing newborns and young children. Available test protocols: Tympanometry with 1 kHz; Tympanometry and Auto Reflex or Tympanometry with Reflex at 80 dB WB.

easyTymp cradle

The easyTymp cradle serves as a docking station and re-charger. It is available as a version with ear tip box or integrated printer.

Extensive Storage

The internal memory of the easyTymp stores more than 1000 measurements. With the optional impedance software data can also be transferred to a PC.

Standard Accessories

easyTymp handheld unit; with Probe tip;
Probe Tip replacement; rechargeable battery;
Power supply unit for easyTymp handheld unit;
Eartip box with eartips; Calibration cavity;
Carrying case

Additional Accessories

MAICO-Impedance Software
External Probe (35 cm)
License for high frequency probe tone of 1 kHz
Cradle with integrated ear tip box, power supply unit and additional rechargeable battery
Cradle with integrated printer, power supply unit and additional rechargeable battery
Wall Mount Kit for cradle



easyTymp with cradle and eartip box

Technical Data

Tympanometer

Probe frequency, -intensity	226 Hz \pm 1%, 69 dB _{HL} in 2 cm ³
Optional	1000 Hz \pm 1%, 69 dB _{HL} in 2 cm ³
Pressure range	+ 200 bis - 400 daPa
Volume range	0,1 bis 8,0 ml
Accuracy	\pm 5% bzw. \pm 10 daPa
Test time	< 3 seconds

Reflex Mode

Test frequencies	500, 1000, 2000, 4000 Hz \pm 3%
Test Method	ipsilateral
Intensities ipsilateral	70 ... 100 dB _{HV}
Intensity setting	automatic or single intensity

Test protocols

	Tymp 226 Hz;
	Tymp 226 Hz + Auto Reflex;
	Tymp 226 Hz + Reflex 90 dB
Opt. High Frequency	additional Tymp 1 kHz;
	Tymp 1 kHz + Auto Reflex;
	Tymp 1 kHz + Reflex 80 dB WB

easyTymp

Memory	1 curve per ear and test.
Internal Memory	> 1000 measurements
Display	Full color graphic LCD-Display
Dimensions / Weight	W x D x H: 80 x 300 x 70 mm / 427 g

Cradle

Dimensions	B x T x H: 150 x 295 x 110 mm
Power	100 - 240 VAC, 50/60 Hz

Optional external Probe

Optional Printer	Probe with status lights
	4 InchThermo printer

Medical CE-mark Standards

	TÜV – identification no. 0123
	IEC 60601-1, Class II, Type B
	IEC 60601-1-2
	IEC 60645-5

Specifications are subject to change without notice



MAICO Diagnostic GmbH
Salzufer 13/14
10587 Berlin, Germany
Tel.: +49 30/70 71 46-50
Fax: +49 30/70 71 46-99
E-Mail: export@maico.biz
Web: www.maico.biz

Distributed by:



1/10 Dorsey Street, Milton, QLD 4064
PO Box 1869, Toowong DC, QLD 4066
Free call: 1800 639 263 F 07 3368 1044
E enquiry@sonici.com.au W www.sonici.com.au