



GSI AUDERA™ AEP/CAEP

AUDITORY EVOKED POTENTIALS



Product Specifications

General Specifications

- Test Types: AEP, ECochG, Cortical AEP, AMLR, EABR
- Transducers: Insert earphones, TDH Headphones, Bone vibrator, Loudspeaker
- Protocols: Default and customer specified
- Marker Sets: Default and customer specified
- Reports: Color, Black/White or PDF

Stimulus Specifications:

- Stimulus Types: Click, tone burst, tone pip
- Stimulus Polarity: Condensation, Rarefaction and Alternating
- Masking Types: Absolute or stimulus relative
- Intensity: 0 to 130 dB SPL
- Repetition rates: 0.2 – 100 depending on modality
- High Pass Filtering: RC or Digital Butterworth
- Low Pass Filtering: Butterworth or Digital linear phase

GSI Audera Amplifier:

- Dimensions: 12.99" (W) x 10.62" (D) x 19.29" (H)
- Weight: .94lb
- Interface To Main Unit: Proprietary high-speed, serial digital
- Number of Channels: 2 Isolated (type BF) for patient safety
- Electrode inputs: Differential
- Electrode connectors: 5 DIN 42802 safety connectors
- Input Impedance: >1000 MW
- Frequency Response: 0.2-10,000 Hz

GSI Audera Main Unit

- Computer Interface: USB - Type I
- Trigger Controls Input/Output: Standard TTL logic level
- Mains Power Supply: 115V, 110V, or 230V; 50-60 Hz
- Power Consumption: 115W, excluding printer

Isolated Power:

- a) Main unit includes isolation transformer/ power supply which provides isolated mains power only for supported notebook computer and inkjet printer models.
- b) Main unit provides isolated power to Amplifier/Digitizer or ProbeUnit.
- Dimensions: 12.99" (W) x 10.62" (D) x 19.29" (H)
- Weight: 7.05lb

Environmental Limits:

- Operating Temp: 50° F to 104° F
Relative Humidity: 30 to 75%, non-condensing
- Storage Temp: -40° F to 158° F
Relative Humidity: 10 to 100%, non-condensing

CPU Recommendation

- Operating System: Windows XP Pro, Vista Business (SP1), Service Pack 2
- Processor: 1.4GHz Celeron or above
- Minimum RAM: 1GHz
- Storage: 20 Gb harddrive
- Additional Storage: CD R/W drive
- Interface: USB (Qty 2)
- Graphics: 1024 x 768 SVGA

Supplied Accessories

- GSI Audera Main Unit
- GSI Audera Reference Manual
- GSI Audera 2-Channel Amplifier with 9' cable
- GSI Audera AEP/CAEP Software Application or Licensing key to activate
- GSI Audera AEP/CAEP User's Manual
- Insert Earphones with 9' cable
- GSI Audera Loop-back cable
- Electrodes, 6mm cup, 12 pk
- Electrodes, 10mm cup, 12 pk
- Electrode Linker
- Disposable side snap electrodes, 25 pk
- Electrode Leads, Snap, 5 pk
- NuPrep Gel, 4 oz. tube
- Ten 20 Paste, 4 oz. tube
- Infant eartips, 3.5mm, 20 pk
- Infant eartips, 4.0mm, 20pk
- 3A foam eartips, 10mm, 100pk
- 3A foam eartips, 13mm, 100pk

Optional Accessories

- GSI Audera Service Manual
- GSI Audera Laptop Computer
- GSI Audera Desktop Computer
- GSI Audera Laptop Power Kit (cables to power through base unit)
- GSI Audera Isolation Transformer (for customer desktop systems)
- GSI Audera EABR cable

Related Part Numbers

- GSI Audera AEP/ASSR System. 2001-9700
- GSI Audera AEP/DPOAE System. 2001-9705
- GSI Audera ASSR/DPOAE System 2001-9710
- GSI Audera AEP/ASSR/DPOAE System 2001-9715
- GSI Audera AEP only System 2001-9720
- GSI Audera ASSR only System. 2001-9725
- GSI Audera DPOAE only System. 2001-9730
- GSI Audera ASSR Upgrade with Amplifier 2001-9661
- GSI Audera ASSR Upgrade without Amplifier 2001-9662
- GSI Audera AEP Upgrade with Amplifier 2001-9663
- GSI Audera AEP Upgrade without Amplifier 2001-9664
- GSI Audera DPOAE Upgrade. 2001-9665

Quality System

- Manufactured, designed, developed and marketed under ISO 13485 certified quality system.

Compliance/Regulatory Standards

- Designed, tested and manufactured to meet the following domestic (USA), Canadian, European and International Standards:
- UL 60601-1 American Standards for Medical Electrical Equipment
 - IEC 60601-1, EN 60601-1 International Standards for Medical Electrical Equipment
 - CSA C22.2 # 601-1-M90
 - Medical Device Directive (MDD) to comply with "EC Directive" 93/42/EEC

Australian Distributer:



SONIC
Everyday Sounds Better

Free Call:
1800 639 263



gsi
Grason-Statler



GSI AUDERA™ ASSR

AUDITORY STEADY STATE RESPONSE

Product Specifications

General Specifications

- Transducers: Insert earphones, TDH Headphones, Bone vibrator, Loudspeaker
- Protocols: Default Asleep and Awake protocols or customer specified – Estimated Audiogram relies on default protocols
- Display: ASSR Thresholds, Estimated Audiogram, Results Summary, Trials Done
- Reports: Color, Black/White or PDF

Stimulus Specifications:

- Stimulus Types: AM/FM
- Masking Types: Absolute or stimulus relative
- Intensity: -10 to 130 dB HL
- Carrier Frequency: 250 – 8000 Hz
- Modulation Frequency: 20 – 200 Hz depending on carrier frequency
- AM Modulation: 0 – 100%
- FM Modulation: 0 – 15%
- Relative Angle: 0 – 359 degrees

GSI Audera Amplifier:

- Dimensions: 12.99" (W) x 10.62" (D) x 19.29" (H)
- Weight: .94lb
- Interface To Main Unit: Proprietary high-speed, serial digital
- Number of Channels: 2 Isolated (type BF) for patient safety
- Electrode inputs: Differential
- Electrode connectors: 5 DIN 42802 safety connectors
- Input Impedance: >1000 MW
- Frequency Response: 0.2 – 10,000 Hz

GSI Audera Main Unit

- Computer Interface: USB - Type I
- Trigger Controls Input/Output: Standard TTL logic level
- Mains Power Supply: 115V, 110V, or 230V; 50-60 Hz
- Power Consumption: 115W, excluding printer

Isolated Power:

- a) Main unit includes isolation transformer/ power supply which provides isolated mains power only for supported notebook computer and inkjet printer models.
- b) Main unit provides isolated power to Amplifier/Digitizer or ProbeUnit.
- Dimensions: 12.99" (W) x 10.62" (D) x 19.29" (H)
- Weight: 7.05lb

Environmental Limits:

- Operating Temp: 50° F to 104° F
Relative Humidity: 30 to 75%, non-condensing
- Storage Temp: -40° F to 158° F
Relative Humidity: 10 to 100%, non-condensing

CPU Recommendation

- Operating System: Windows XP Pro, Vista Business (SP1)
- Processor: 1.4GHz Celeron or above
- Minimum RAM: 1GHz
- Storage: 20 Gb harddrive
- Additional Storage: CD R/W drive
- Interface: USB (Qty 2)
- Graphics: 1024 x 768 SVGA

Supplied Accessories

- GSI Audera Main Unit
- GSI Audera Reference Manual
- GSI Audera 2-Channel Amplifier with 9' cable
- GSI Audera ASSR Software Application or Licensing key to activate
- GSI Audera ASSR User's Manual
- Insert Earphones with 9' cable
- GSI Audera Loop-back cable
- Electrodes, 6mm cup, 12 pk
- Electrodes, 10mm cup, 12 pk
- Electrode Linker
- Disposable side snap electrodes, 25 pk
- Electrode Leads, Snap, 5 pk
- NuPrep Gel, 4 oz. tube
- Ten 20 Paste, 4 oz. tube
- Infant eartips, 3.5mm, 20 pk
- Infant eartips, 4.0mm, 20pk
- 3A foam eartips, 10mm, 100pk
- 3A foam eartips, 13mm, 100pk



Optional Accessories

- GSI Audera Service Manual
- GSI Audera Laptop Computer
- GSI Audera Desktop Computer
- GSI Audera Laptop Power Kit (cables to power through base unit)
- GSI Audera Isolation Transformer (for customer desktop systems)

Related Part Numbers

- GSI Audera AEP/ASSR System..... 2001-9700
- GSI Audera AEP/DPOAE System..... 2001-9705
- GSI Audera ASSR/DPOAE System .. 2001-9710
- GSI Audera AEP/ASSR/DPOAE System 2001-9715
- GSI Audera AEP only System 2001-9720
- GSI Audera ASSR only System..... 2001-9725
- GSI Audera DPOAE only System..... 2001-9730
- GSI Audera ASSR Upgrade with Amplifier 2001-9661
- GSI Audera ASSR Upgrade without Amplifier 2001-9662
- GSI Audera AEP Upgrade with Amplifier 2001-9663
- GSI Audera AEP Upgrade without Amplifier 2001-9664
- GSI Audera DPOAE Upgrade..... 2001-9665

Quality System

- Manufactured, designed, developed and marketed under ISO 13485, ISO 9001 certified quality system.

Compliance/Regulatory Standards

- Designed, tested and manufactured to meet the following domestic (USA), Canadian, European and International Standards:
- UL 2601-1 American Standards for Medical Electrical Equipment
 - IEC 601-1, EN 60601-1 International Standards for Medical Electrical Equipment
 - CSA C22.2 # 601-1-M90
 - Medical Device Directive (MDD) (ID No.: 0086) to comply with "EC Directive" 93/42/EEC

Distributed by:



1/10 Dorsey Street, Milton, QLD 4064
 PO Box 1507, Milton, QLD 4066
 Free call: 1800 639 263 F 07 3368 1044
 E enquiry@sonici.com.au W www.sonici.com.au





GSI AUDERA™ DPOAE

DISTORTION PRODUCT OTOACOUSTIC EMISSIONS

Product Specifications



General Specifications

- Test Types: Distortion Product Otoacoustic Emissions, Spontaneous OAE, Input/Output DPOAE
- Protocols: Default Diagnostic and Screening, Customer Configurable
- Display: DPgram, FFT plot, I/Ogram, Signal/Noise Ratio of selected point, Compare Test (sequential test comparisons, multiple test, multiple days)
- Reports: Color, Black/White or PDF
- DPOAE Stimulus Tones:
 - Frequency: 500 – 12, 000 Hz
 - Level: 20 – 80 dB SPL, in 5 dB steps
 - Accuracy: ± 3 dB
 - Harmonic Distortion: ≤ 1.8% at 80 dB SPL, IEC 711 coupler, 500 – 12,000 Hz
 - Dynamic Range: 85 dB SPL, IEC 711 coupler, 500-12,000 Hz, F1 & F2 = 65 dBSPL
 - Octave Ranges: 500-1000, 1000-2000, 2000-4000, 4000-8000, 8000-12000 Hz
 - Points per Octave: 1 – 12 points
 - F2/F1 Ratio: 1.1 – 1.8
- Test Time: Varies, depending on test parameters, environment, and scoring options

Status Indicators:

- Probe LED:
 - Green solid – test in progress
 - Yellow solid – seal check in progress
 - Yellow flashing – test stopped, probe problem/ seal check failed

OAE Pod/Probe:

- Dimensions: 1.69”(W) x 1.18”(D) x 4.17”(H)
- Weight: .44lb
- Interface to GSI Audera Base: 25 pin D-SUB connector

GSI Audera Main Unit

- Computer Interface: USB - Type I
- Trigger Controls Input/Output: Standard TTL logic level
- Mains Power Supply: 115V, 110V, or 230V; 50-60 Hz
- Power Consumption: 115W, excluding printer

Isolated Power:

- a) Main unit includes isolation transformer/ power supply which provides isolated mains power only for supported notebook computer and inkjet printer models.
- b) Main unit provides isolated power to Amplifier/Digitizer or ProbeUnit.
- Dimensions: 12.99”(W) x 10.62”(D) x 19.29”(H)
- Weight: 7.05lb

Environmental Limits:

- Operating Temp: 50° F to 104° F
- Relative Humidity: 30 to 75%, non-condensing
- Storage Temp: -40° F to 158° F
- Relative Humidity: 10 to 100%, non-condensing

CPU Recommendation

- Operating System: Windows XP Pro, Vista Business (SP1)
- Processor: 1.4GHz Celeron or above
- Minimum RAM: 1GHz
- Storage: 20 Gb harddrive
- Additional Storage: CD R/W drive
- Interface: USB (Qty 2)
- Graphics: 1024 x 768 SVGA

Supplied Accessories

- GSI Audera Main Unit
- GSI Audera Reference Manual
- GSI Audera OAE Probe/Pod with Test Cavity
- GSI Audera OAE Calibration CD
- GSI Audera DPOAE Software Application or Licensing key to activate
- GSI Audera DPOAE User's Manual
- GSI Audera Shoulder Mount Kit
- Eartip Kit, Infant
- Eartip Kit, Child/Adult
- Eartip Kit, Adult
- Probe Cleaning Floss & Instructions

Optional Accessories

- GSI Audera Service Manual
- GSI Audera Laptop Computer
- GSI Audera Desktop Computer
- GSI Audera Laptop Power Kit (cables to power through base unit)
- GSI Audera Isolation Transformer (for customer desktop systems)

Related Part Numbers

- GSI Audera AEP/ASSR System. 2001-9700
- GSI Audera AEP/DPOAE System. 2001-9705
- GSI Audera ASSR/DPOAE System 2001-9710
- GSI Audera AEP/ASSR/DPOAE System 2001-9715
- GSI Audera AEP only System 2001-9720
- GSI Audera ASSR only System. 2001-9725
- GSI Audera DPOAE only System 2001-9730
- GSI Audera ASSR Upgrade with Amplifier 2001-9661
- GSI Audera ASSR Upgrade without Amplifier 2001-9662
- GSI Audera AEP Upgrade with Amplifier 2001-9663
- GSI Audera AEP Upgrade without Amplifier 2001-9664
- GSI Audera DPOAE Upgrade. 2001-9665

Quality System

- Manufactured, designed, developed and marketed under ISO 13485 certified quality system.

Compliance/Regulatory Standards

- Designed, tested and manufactured to meet the following domestic (USA), Canadian, European and International Standards:
- UL 60601-1 American Standards for Medical Electrical Equipment
 - IEC 60601-1, EN 60601-1 International Standards for Medical Electrical Equipment
 - CSA C22.2 # 601-1-M90
 - Medical Device Directive (MDD) to comply with "EC Directive" 93/42/EEC

Distributed by:



1/10 Dorsey Street, Milton, QLD 4064
 PO Box 1507, Milton, QLD 4066
 Free call: 1800 639 263 F 07 3368 1044
 E enquiry@sonici.com.au W www.sonici.com.au

